






适用范围:

技术特点:



0.1-50

主要技术参数:

RCDB :

	mm	h mm	mT	mm	kw	m/s	kg	mm			
								A	B	D	d
RCDB- 5	500	150	60	90	1	4.5	360	280	325	630	450
RCDB- 6	600	175	60	120	1.6		480	280	325	740	500
RCDB- 6.5	650	200	70	150	2		560	305	400	780	640
RCDB- 8	800	250	70	200	3.6		800	310	400	960	780
RCDB- 10	1000	300	70	250	5		1350	310	400	1300	920
RCDB- 12	1200	350	70	300	6.8		2000	338	425	1500	1140
RCDB- 14	1400	400	70	350	9		2500	336	440	1600	1200
RCDB- 16	1600	450	70	400	13		4800	500	570	1850	1400
RCDB- 18	1800	500	70	450	18		6100	530	610	2150	1800

RCDB- T :

		mm	mm	mT	kw	m/s	mm		kg
							D	B	
RCDB- 6.5	T1	650	200	90	4	5.8	960	390	800
	T2			120	6		960	480	1450
	T3			150	10		1000	550	2120
RCDB- 8	T1	800	250	90	5.3		1200	400	1360
	T2			120	7.5		1200	450	1920
	T3			150	11.5		1300	520	2000
RCDB- 10	T1	1000	300	90	7.1		1300	450	2450
	T2			120	9		1300	540	3010
	T3			150	14		1500	560	2500
RCDB- 12	T1	1200	350	90	9		1500	480	3290
	T2			120	13.5	1500	560	4100	
	T3			150	16	1600	620	5300	
RCDB- 14	T1	1400	400	90	11.5	1750	580	3700	
	T2			120	18	1750	700	5100	
	T3			150	25	1950	880	6500	
RCDB- 16	T1	1600	450	90	18	1900	620	5800	
	T2			120	25	1950	680	7100	
	T3			150	40	2000	850	9320	
RCDB- 18	T1	1800	500	90	25	2150	920	7350	
	T2			120	32	2200	1030	9200	
	T3			150	45	2200	1030	13800	
RCDB- 20	T1	2000	550	90	30	2200	1030	8600	
	T2			120	40	2350	1080	13500	
	T3			150	50	2650	1320	17200	

